



Sand Star I

Groom Your Bunkers with Ease

The Sand Star I stands as the preferred bunker and sand rake for golf course superintendents and grounds directors seeking exceptional traction, enhanced stability, and an extensive array of implements. Crafted with industrial-grade materials, the Sand Star I is designed for long-lasting performance at your facility. With a versatile selection of over 50 accessories and industrial-grade components, the Sand Star I can be customized to suit the distinctive requirements of your course.

• PERFORMANCE

Optimal raking and progressive throttling is achieved with the "Speed Boss" Speed Control System. You not only spend less time fixing mistakes but your course is left in ideal condition.

• PRODUCTIVITY

Center and rear implements, plows, key switches, and other controls are located conveniently in the operator position, which has been ergonomically designed for safety, comfort, and productivity. With the Sand Star I, you never have to leave the machine.

• OPTIONS

With over 50 accessories and industrial-grade components, Smithco's bunker rakes and groomers are built to last as your course changes and grows.

• INTERCHANGEABILITY

Smithco's Sand Star's are equipped with a single point quick hitch for easy interchangeability of implements and attachments. You spend less time maneuvering equipment and more time getting the job done.

Exceptional Service and Products Since 1967
smithco.com

Smithco
WE TAKE YOUR TURF SERIOUSLY

Sand Star I

SPECIFICATIONS

Smithco

United States | 877.833.7648
International | +1 610.688.4009

ENGINE

Type	Vanguard V-twin air cooled
Displacement	29.3 in ³ (480 cc)
Rated Horsepower	16 hp (11.9 kW)
Air Cleaner	Engine mount and remote cyclonic
Cooling	Air-cooled
Lubrication	Full pressurized
Oil Filter	Full flow; Spin on type
Electrical System	16 amp, with 12V 300 CCA battery, fuse protected
Fuel Capacity	5 gal (18.9 l)

TRACTION DRIVE

Traction System	Variable displacement hydraulic pump; Individual hydraulic wheel motors on rear
Hydraulic System	5 gal (18.9 l)
Hydraulic Cooling	Full flow filter with oil

TIRES, BRAKES & STEERING

Tires	22-11 x 10.0 Knobby Tire
Service Brakes	Hydrostatic
Parking Brake	Hand operated, 8 in (20 cm) disk type
Steering	Manual chain drive front wheel steering

SPEED

Transport	0-12 mph (0-19.3 kph)
Reverse	0-5 mph (0-8 kph)

WEIGHTS & DIMENSIONS

Weight	875 lbs (397 kg)
Length	68 in (v 1.7 m)
Width	58 in (1.5 m)
Height	52 in (1.3 m)
Ground Clearance	5.5-7 in (13-18 cm)
Wheelbase	68 in (1.7 m)



Learn More Today!